

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Recs Vol 17 Pg 7384  
-----  
Set post, cor. secs. 25, 26, 35, & 36, from which  
A fir, 12" dia., bears S.20°W., 20 lks.  
A fir, 6" dia., bears S.15°E., 20 lks.  
A fir, 9" dia., bears N.30°E., 23 lks.  
A cedar, 18" dia., bears N.1°W., 243 lks.

GL0 survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7412)  
-----  
Cor. to secs. 25, 26, 35 and 36. This post cor. is charred by fire. I find two of the witness trees. At cor point, I set a stone, 20x10x8" in mound of stone, as it is too rocky to set it in the ground. For cor. to secs. 25, 26, 35 and 36, marked with 1 notch on S and E edges, from which  
A Cedar, 18" dia., bears N.1°W., 243 lks, marked T30S R9W S26 BT.  
A Fir, 12" dia. bears S.20°W., 20 lks. mkd T30S R9W S35 BT  
These are the original witness trees.  
I mark  
A Fir, 20" dia., bears N.41½°E., 25½ lks., mkd T30S R9W S25 BT.  
A Yellow Pine, 36" dia., bears S.59°E., 173 lks., marked T30S R9W S36 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby - Jack Barnett - Oct. 1964 - C.S. File 53/53-44  
-----  
Found - 3 old BTs & rotted remains of other and Corner Stone  
18" now 42" Cedar N.1°W. 160.6 ft. shows scar.  
12" Fir S.20°W. 13.2 ft., down & very badly rotted.  
20" now 36" N.41½°E. 16.8 ft. open & find "B" scribe  
36" now 4" Pine S.59°E. 114.2 ft., shows scar.  
Set Brass Cap at Cor. Mkd: County Surveyors T30S R9W S26|S25  
Office, 1964 S35|S36  
New BTs- 9" D.Fir S.45°E. 25.9 ft. Mkd: T30S R9W S36 CS BT.  
8" Fir South 14.2 ft. mkd: T30S R9W S35 CS BT.  
13" D.Fir N.19°W. 20.5 ft. Mkd: T30S R9W S26 CS BT.  
15" D.Fir N.70°E. 23.8 ft. mkd: T30S R9W S25 CS BT.

BLM Dependent resurvey by Dale T. Bedell, Wayne L. Rogers, & Boyd W. Peterson, Cadastral Surveyors under Group #1339, surveyed Aug/Nov. 1986 - (DCSO records Vol. 48 Pages 18358-9)  
-----  
The cor. of secs. 25, 26, 35 and 36, perpetuated and recorded by Tracy, in 1964, monumented with an iron post, 1½" cont.

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

dia, firmly set, projecting 12" above ground, and in a mound of stone, 3 ft. base, to top, with brass cap (properly) mkd. from which an original bearing tree  
A cedar, 47" dia, bears N.1°W., 249 lks., with healed blaze. (Record 243 lks.)  
and the remains of the bearing trees mkd. by Bushey  
A fir, 38" dia, bears N.41½°E., 25½ lks., with illegible scribe marks visible on an opened blaze.  
A decayed pine stump, 40" dia, bears S.59°E., 178 lks., with scribe marks 5 B visible on a burnt blaze. (Record 173 lks.)  
and bearing trees mkd. by Tracy  
A fir, 16" dia, bears N.70°E., 37 lks., with healed blaze.  
A fir, 11" dia, bears S.45°E., 40 lks. w/two healed blazes  
A fir, 10" dia, bears South 22 lks., w/two healed blazes  
A fir, 15" dia, bears N.19°W., 31 lks., with healed blaze.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates  
Professional Land Surveyors - 2024 - M185-28  
-----  
Found - Ok per record D.C.S.O. Vol 17 pg 7384, D.C.S.O. C.S. file 53/53-44, & D.C.S.O. Vol 48 pgs 18358-9.  
A Fir 39" diam bears N.50°E. 16.6' to a nail at left side center with healed blaze and Roseburg loc poster.  
New - Added paint, blazes, nails, (per above locations), and tags to rev of Bts.  
Added post N. 5' and E. 5' with boundary signs.