

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7385</p> <p>-----</p> <p>Set ¼ sec. post, in edge of creek, from which A fir, 24" dia., bears N.19°W., 32 lks. An Alder, 15" dia., bears S.45°E., 39 lks.</p>
<p>Howard W. Johnstone - For: Roseburg Lumber Co. - May 28, 1964 - C.S. File 51/163-12</p> <p>-----</p> <p>Found - 24" Fir, now 38" N.19°W., 21.1 ft. bark scribe visible. Tree blown down. New BTs- 11" W.Fir S.14°W., 78.6 ft. 8" W.Fir S.75°E., 70.5 ft. Note - Corner falls in west edge of 12 Mile Creek so no pipe was set.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-63</p> <p>-----</p> <p>Found - BTs as listed below & recorded in 1964 11" W.Fir S.14°W., 78.6 ft. mkd: ¼ S BT. 8" W.Fir S.75°E., 70.5 ft. mkd: ¼ S BT. Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1964 T30S R9W ¼ S26 S25</p>
<p>BLM Dependent resurvey by Dale T. Bedell, Wayne L. Rogers, & Boyd W. Peterson, Cadastral Surveyors under Group #1339, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18359)</p> <p>-----</p> <p>The ¼ sec. cor. of sees. 25 and 26, perpetuated and recorded by Johnstone, in 1964, and further perpetuated and recorded by Tracy, in 1964, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree A fir root crown, bears N.19°W., 32 lks., no marks remain. and a bearing tree mkd. by Johnstone. A fir, 15" dia, bears S.78°E., 107 lks., with healed double blaze. and a new bearing tree An alder, 8" dia, bears S.60°W., 15½ lks., mkd. ¼ S26 BT on the bark.</p>
<p>Fd. Ok by D.Edwards 2/2007 - M152-35</p>
<p>continued next page</p>

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-28

Found - Ok per record.
Set - A Fir 20" diam bears N.18¾°E. 136.7' scribed
"¼S25BT"
A flat boulder 6'x6x1' bears S.54¾°E. 29.2' to a
nail in center of chiseled "X" on top center
with LS washer 90216.
A Fir 11" diam bears N.66½°W. 20.0' to a nail at
right side center scribed "¼S26BT" with LS
washer and tag by 90216 10/2/24 and tag on
reverse.
Added - Post S. 2.5' and N. 5.0' with boundary signs.