

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7387

Set ¼ sec. post from which
 A laurel, 4" dia., bears N.60°W. 37 lks.
 A fir, 18" dia., bears S.87°E. 55 lks.

Howard W. Johnstone - For: Roseburg Lumber Co. - Jan. 7, 1961
- C.S. File 51/163-4

Found - 18" D.Fir S.87°E., 36.3 ft. now 40", scribe visible.
Set - Corner falls in area of proposed road reconstruction
 therefore an iron pipe was not set at this time.
 7" D.Fir N.73°W., 94.3 ft.
 20" Cedar N.73°E., 113.7 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-67

Found at cor. trees recorded in 1961. Using the recorded bearings we cannot bring distances to & intersection.
We set 1" IP & brass cap mkd: COUNTY SURVEYORS OFFICE 1964 T30S R9W ¼ S14|S13.
Existing BTs as follows:
 7" D.Fir N.73°W., 86.6 ft.
 20" Cedar N.73°E., 116.0 ft.
This corner lies on West side of new 12 mile creek road.

DCSO fd. ok VRT - 7/31/1970 - C.S. File 53/53-75

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - July 19, 1973 - C.S. File 56/34-13

Found - 1964 DCS brass cap in place.
 20" cedar N.73°E., 116.0 ft. Alive, good cond.
 scribe visible on unhealed blaze.
 BT to NW was destroyed by logging.
New BT - 6" D.Fir N.20°W., 20.3 ft. mkd: "¼ S14 CS BT"

Fd. Ok 6/1988 - H. Johnstone, M106-52

continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, under Group No. 2009 surveyed July/Aug. 2002 - (DCSO records Vol. 54 Page(s) 21071)

The ¼ sec. cor. of secs. 13 and 14, perpetuated by Johnstone, in 1961, remonumented by Tracy, in 1964, from original evidence no longer existent, perpetuated by Tracy in 1973, and recovered by Johnstone in 1988, monumented with an iron post, 1¼" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd.

from which the remaining BT mkd. by Johnstone in 1961

A cedar, 25" dia., bears N.73°E., 116.0 ft., with healed double blaze.

and bearing tree mkd. by Tracy in 1973

A fir, 12" dia., bears N.20°W., 20.3 ft., with healed blaze.

The geographic position (NAD 1983 (CORS)) of the ¼ section corner of sections 13 and 14, as determined from a tie to National Geodetic Survey stations DODSON BUTTE CORS ARP and CAPE BLANCO CORS ARP, is as follows:

Latitude: 42°57'36.68" N. Longitude: 123°43'18.92" W.

Gary Smither - For: Moore Mill & Lmbr Co. & Rsbg Resources Co. - 10/2006 - M151-57

Found - 1964 county brass cap

BTs - 12" D.Fir N.20°W., 20.3 ft. W/healed face & alum tag
26" Cedar N.73°E., 116.0 ft. W/healed face & alum tag

New BTs- 7" D.Fir S.22°W., 15.8 ft. To spike side center & alum tag, scribe T30R9 ¼S14BT

12" D.Fir S.70°W., 17.2 ft. to spike side center & alum tag, scribe T30R9 ¼S14BT