

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7388

Set ¼ sec. post, from which
 A W.Oak, 10" dia., bears S.15°W. 13 lks.
 A W.Oak, 12" dia., bears S.75°E. 26 lks.

Howard W. Johnstone - For: Roseburg Lumber Co. - Nov. 1988 - M101-44

Set - 5/8"x36" iron rod & alum. cap mkd: ¼ S11|S12 in mound of stone.
 6" Oak N.81°W., 29.5 ft. "¼ S11 BT"
 10" Fir S.84°E., 12.9 ft. "¼ S12 BT"

Tony Hostetter - For: Roseburg Resources Co. Co. - May/July 2003 - M142-69

Set - 5/8" x 30" rebar w/ 2½" alum. cap.
Scribed- "¼ S12 BT" on an 18" DF bears N.70°E., 38.5 ft.
 "¼ S12 BT" on a 13" DF bears S.34°E., 20.0 ft.
 "¼ S11 BT" on an 11" DF bears S.4°W., 15.5 ft.
 "¼ S11 BT" on an 11" DF bears S.77°W., 37.8 ft.
Note - Per narrative - some corners established on M101-44 were set incorrect. The W¼ S12 monument was pulled & cap removed - per Roseburg Resources request. (1988 Ren.)

FD. Ok by T. Hostetter, 1/2007 - M152-28