TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7384

Set ¼ sec. post, from which
A laurel, 15" dia., bears S.45°W., 53 lks.
A laurel, 20" dia., bears N.30°W., 40 lks.

BLM Dependent resurvey by Dale T. Bedell, Wayne L. Rogers, & Boyd W. Peterson, Cadastral Surveyors under Group #1339, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18358)

Point for the ¼ sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked: T30S R9W
¼ S 25 / S 36
1986

from which
A fir, 4" dia., bears N.25½°E., 90 lks., mkd: X BT.
A fir, 7" dia., bears S.48½°E., 25 lks., mkd: ¼ S36 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-28

Found ok per record.
New - 7" Fir S.53°E. 5.0' to a nail scribed "X BT"
11" Fir bears S.86¼°W. 23.3' to a nail scribed "¼S36BT"
12" Fir bears N.13¼°W. 14' to a nail scribed "¼S25BT"
New - Added LS washer & tag by 90216 9/30/24 to new Bts.
Straightened mon and backfilled with dirt to 0.6' above ground.
Added post W. 5' and E. 5' with boundary signs.