TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7385

Set ¼ sec. post, from which
A laurel, 12" dia., bears S.73°W., 115 lks.
A fir, 12" dia., bears N.66°E., 115 lks.

BLM Dependent resurvey by Dale T. Bedell, Wayne L. Rogers, & Boyd W. Peterson, Cadastral Surveyors under Group #1339, surveyed Aug/Nov 1986 - (DCSO records Vol 48 Page(s) 18361-2)

The ¼ sec. cor. of secs. 24 & 25, determined from the remaining original bearing tree:
A sawed fir stump, 36" dia., bears N.66°E., 115 lks., with reverse scribe mark B visible on the overgrowth of an opened blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T30S R9W ¼ S 24 / S 25 1986

from which new BTs
A fir, 6" dia., bears N.62½°E., 44½ lks., mkd: ¼ S24 BT.
A fir, 19" dia., bears S.55½°E., 36½ lks., mkd: ¼ S24 BT.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-28

Found ok per record.