TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7387

Set ¼ sec. post from which
A fir, 30" dia., bears S.8°W., 55 lks.
A fir, 20" dia., bears N.58°W., 84 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Aug. 1964 - C.S. File 53/53-57

Found - Squared post & orig. BTs as follows:
30" now 42" D.Fir S.8°W., 36.3 ft. showing good "¼S" bark scribe.
20" now 36" D.Fir N.50°W., recorded as N.58°W., 55.4 ft. showing parts of "¼" bark scribe.
Set Brass cap at cor. mkd: COUNTY SURVEYORS T30S R9W ¼ S 13
OFFICE 1964 S 24
New BTs- 14" D.Fir S.52°E., 7.9 ft. mkd: ¼ S24 CS BT.
18" D.Fir N.51°W., 3.0 ft. mkd: ¼ S13 CS BT.

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, under Group No. 2009 surveyed July/Aug. 2002 - (DCSO records Vol. 54 Page(s) 21068)

The ¼ sec. cor. of secs. 13 & 24, remonumented by Tracy, in 1964, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees
A sawed fir stump, 49" dia., bears S.4¾° W., 38.0 ft., with axe marks visible and healed blaze. (Record, S.8°W., 36.3 ft.)
A sawed fir stump, 38" dia., bears N.49½°W., 55.4 ft., with no marks visible. (Record, N.58°W.)
and bearing trees mkd. by Tracy
A fir, 21" dia., bears S.54°E., 7.5 ft., with healed blaze.
A fir, 25" dia., bears N.48¼°W., 3.0 ft., with healed blaze.