

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Howard W. Johnstone - For: Roseburg Lumber Co. - June 1988 - M106-51

-----

Set - 5/8"x44" iron rod with alum cap marked C $\frac{1}{4}$  LS 498  
New BTs- 15" Fir S.59 $\frac{1}{2}$ °W., 7.9 ft.  
12" cedar N.4°W., 24.0 ft.  
 $\frac{3}{4}$ " IP bears N.13°41'11"W., 4.49 ft.

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, under Group No. 2009 surveyed July/Aug. 2002 - (DCSO records Vol. 54 Page(s) 21074)

-----

The center  $\frac{1}{4}$  sec. cor. of sec. 13, established by Johnstone in 1988, and is accepted as the corner, monumented with a rebar, 5/8" dia., firmly set, projecting 15" above ground, with alum. cap mkd.

T30S R.R.CO. R9W  
S13  
C 1/4  
1988  
LS498

from which

A fir, 17" dia., bears S.58°W., 7.6 ft., with healed blaze.

A cedar, 16" dia., bears N.4°W., 24.0 ft., with healed blaze.

From this point, an iron pipe,  $\frac{3}{4}$ " dia., firmly set, projecting 5" above ground, with no cap, set by persons unknown, bears N.17°10'34"W., 4.63 ft. This point was not utilized in the course of this survey.