

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; and 31, T30-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7372)

Set ¼ sec. post, from which
A Fir 15" dia., bears N.52°W., 32 lks. dist.
A Fir 5" dia., bears N.28°E., 16 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Aug. 1968 - C.S. File 53/67-2

Found - Orig. 15" now 36" Fir, alive, N.52°W., 21.1 ft.,
open and shows "B¼", bark scribe.
Find depression at approx. location of NE. BT, tree
gone.

Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
9W ¼ S36 | S31 8W
1968

New BTs- 7" Hemlock N.36°E., 16.7 ft. mkd. ¼ S31 CS BT.
8" Hemlock S.6°W., 13.8 ft. mkd. ¼ S31 CS BT.
Corner lies on moderate NE. slope.

Fd. BC & 3 BTs by Don Garrett - For: US Dept. Interior, BLM,
contract No. 53500-CT2-334(N) - Sept 1972 Filed 2/10/1982
(added to record 10/2/2023)- M91-10