

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T30-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7371)

Set post, cor. secs. 24, 25, 19 and 30, from which
A Fir 20" dia., bears S.66°E., 45 lks. dist.
A Fir 6" dia., bears S.32°W., 27 lks. dist.
A Fir 12" dia., bears N.42°E., 112 lks. dist.
A Fir 24" dia., bears N.15°W., 122 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1964 - C.S. File 53/53-61

Found - Orig. 20" now 40" D.Fir S.66°E., 29.7 ft., shows very old bark scribe "3S R8W S" & BT scar.
Orig. 6" now 30" W.Fir S.32°W., 17.8 ft., did not open.
Orig. 12" now 22" D.Fir N.42°E., 73.9 ft., shows good scar. Didn't open.
Orig. 24" now 48" D.Fir N.15°W., 80.5 ft., shows faint bark scribe.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S
R9W S 24 | S 19 R8W
S 25 | S 30
1964

New BTs- 13" D.Fir N.44°E., 10.5 ft. mkd. T30S R8W S19 CSBT
11" W.Fir N.39°W., 32.3 ft. mkd. T30S R9W S24 CSBT
30" W.Fir S.32°W., 17.8 ft. mkd. T30S R9W S25 CSBT
9" Yew S.43°E., 30.6 ft. mkd. S30 CS BT.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1021, surveyed April 1980 - (DCSO records Vol. 45 Page(s) 17278-79)

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1339, surveyed Aug/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18355-56)

The Sec. Cor., perpetuated and recorded by Tracy in 1964, monumented with an iron post 1½" dia, firmly set, projecting 12" above ground, with brass cap mkd. in 1964 from which the remains of the original bearing trees:
A Fir 25" dia., bears N.42°E., 110 lks. dist. with healed blaze. (Rec. 112 lks.)
A Fir 42" dia., bears S.66°E., 47 lks. dist. with healed blaze. (Rec. 48 lks.)
(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A root hole bears S.32°W., 27 lks. dist. with a downed Fir 23" dia., lying alongside, with healed blaze.
A Fir stump 52" dia., bears N.15°W., 122 lks. dist., with healed blaze.
and the remains of the bearing trees mkd. by Tracy:
A Fir 15" dia., bears N.35½°E., 15½ lks. dist., with healed double blaze.
A Yew 10" dia., bears S.42½°E., 46 lks. dist., with scribe marks S30 CS BT visible on an open blaze.
A sawed Fir stump 12" dia., bears N.39¼°W., 49 lks. dist., with scribe marks 30S R9W S24 visible on a partially healed blaze.
and new bearing trees:
A Fir 9" dia., bears S.36°W., 104 lks. dist. mkd. T30S R9W S25 BT.
A Fir 6" dia., bears N.27°W., 85½ lks. dist. mkd. T30S R9W S24 BT.

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew -
For: US Department of Interior, BLM Beetle Battle South-Task D -May
25, 2023 - M178-74 A-D

Found - A 2½" County Surveyor's Office brass cap (properly marked) 0.8 ft above ground from which:
A 23" Fir bears N.35½°E., 9.9 ft with healed double blaze and BT sign (1964)
A 42" stump bears S.66°E., 31.4 ft with healed blaze and Roseburg Timber and BT signs (1855)
A roothole bears S.40°E., 30.1 ft with 8" trunk alongside, with partial healed blaze (1964)
A roothole bears S.32°W., 17.8 ft with 23" trunk alongside (1855)
A 17" Fir bears S.36°W., 68.7 ft with healed blaze and BT signs (1986)
A roothole bears N.39¼°W., 33.7 ft, no tree remains (1964)
An 11" Fir bears N.27°W., 56.4 ft with healed blaze and BT sign (1986)
A 52" stump bears N.15°W., 80.5 ft with healed blaze (1855)
A 25" stump bears N.42°E., 72.6 ft with metal top and BT sign (1855)
Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs
New - A 6" Fir bears S.44°E., 10.3 ft mkd: T30S R8W S30 BT Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT

continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T30-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-28

Found - Brass cap, 1855 BTs per rec, 2023 BT per rec.
A Fir 24" diam bears N.45½°E. (N.35½°E.) 9.9' with
healed blaze.
A Fir 19" diam bears S.36°W. 68.7' with visible
scribe.
A dead Fir 11" diam bears N.21°W. (N.27°W.) 56.7'.
New - A Fir 17" diam bears N.21°W. 41.5' scribed
"T30SR9WS24BT"
Added post south 4.3' and west 3.3'.