

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T30-8

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7371)

-----  
Set ¼ sec. post, from which  
A W.Oak 12" dia., bears N.50°W., 94 lks. dist.  
A W.Oak 12" dia., bears S.2°E., 171 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1021, surveyed April 1980 - (DCSO records Vol. 45 Page(s) 17280)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 30 S  
R 9 W R 8 W  
1/4  
S 24 | S 19  
1980

from which  
A Fir 13" dia., bears S.28°E., 7½ lks. dist. mkd. ¼ S19 BT  
A Fir 13" dia., bears N.56½°W., 24 lks. dist. mkd. ¼ S24 BT.

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM Beetle Battle South-Task D -May 24, 2023 - M178-74 A-D

-----  
Found - 3¼" BLM brass cap (properly mkd), 0.3 ft above ground from which:  
A 15" Fir, dead, bears S.28°E., 5.4 ft., with healed double blaze and BT sign (1980)  
A roothole bears N.56½°W., 15.9 ft., trunk alongside mkd: ¼ S24 BT (1980)  
Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)  
New - A 12" fir bears N.80°W., 10.1 ft. mkd: ¼ S24 BT  
A 10" Oak bears N.22°E., 11.0 ft. mkd: ¼ S19 BT.  
Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BTs)