

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7370)

-----  
Set post cor. secs. 7, 18, 12 and 13, from which  
A Pine 20" dia., bears N.12°W., 29 lks. dist.  
A Fir 18" dia., bears N.45°E., 50 lks. dist.  
A Fir 20" dia., bears S.48°E., 114 lks. dist.  
A Chinquapin 12" dia., bears S.68°W., 14 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - S. Bilow, crew - July 9, 1958 - C.S. file 49/100-3

-----  
Found - Orig. 20" now 24" Pine stump, N.12°W., 19.1 ft. I open and find good scribe "BT"  
Orig. 18" now 28" W.Fir snag has good bark scribing, N.45°E., 33.0 ft.  
Orig. 20" now 30" R.Fir, has good bark scribing.  
No trace of orig. SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S  
R9W S 12 | S 7 R8W  
S 13 | S 18  
1958

New BTs- 8" R.Fir bears N.89°W., 9.4 ft. scribed S12 T30S R9W CS BT.  
9" Chinquapin S.43°W., 35.6 ft. scribed S13 T30S R9W CS BT.  
10" R.Fir bears S.30°E., 9.9 ft. scribed S18 T30S R8W CS BT.  
4" W.Fir bears N.73°E., 28.7 ft. scribed S7 CS BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1964 - C.S. File 53/53-54

-----  
Found - Brass cap and 3 BTs as recorded in Byron in 1958.  
NW BT, down.  
New BT - 12" W.Fir N.71°W., 54.6 ft. mkd. T30S R9W S12 CS BT

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1339, surveyed Aug/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18356)

-----  
The Sec. Cor., perpetuated and recorded by Byron in 1958, and further perpetuated and recorded by Tracy in 1964, monumented with an iron post 1½" dia., firmly set, projecting 15" above ground with brass cap mkd. in 1958  
(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the original bearing trees:  
A Fir stump 40" dia., bears S.48°E., 117 lks. dist. with healed blaze. (Rec. 114 lks.)  
A rotted Pine stump 15" dia., bears N.12°W., 30 lks. dist., with scribe marks BT visible on a rotted blaze. (Rec. 29 lks.)  
A rotted Fir stump size indeterminate, bears N.45°E., 50 lks. dist., no marks remaining.  
and the remains of the bearing trees mkd. by Byron:  
A Fir 12" dia., bears N.73°E., 44 lks. dist., with healed blaze.  
A Fir 16" dia., bears S.30°E., 16 lks. dist., with healed blaze.  
A Chinquapin 13" dia., bears S.43°W., 54 lks. dist., with a rotted blaze.  
A root hole bears N.89°W., 14 lks. dist., with a downed Fir, 9" dia., lying alongside, with scribe marks R9W CS visible on a rotted blaze.  
and a bearing tree mkd. by Tracy:  
A Fir 21" dia., bears N.71°W., 83 lks. dist., with two healed blazes.  
and a new bearing tree:  
A Fir 4" dia., bears N.22°W., 22 lks. dist. mkd. X BT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2009, surveyed July/Aug. 2002- (DCSO rec. Vol. 54 Page(s) 21066-7)

-----  
The cor. of secs. 7, 12, 13, & 18, on the E. bdy. of the Tp., monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees  
A decayed stump, size & species indeterminate, bears N.45°E., 35.3 ft., with healed blaze. (Record, fir, 33.0 ft.)  
A decayed stump, size & species indeterminate, bears S.48°E., 77.2 ft., with healed blaze. (Record, fir)  
A decayed stump, size & species indeterminate, bears N.12°W., 19.8 ft., with scribe marks BT visible on decayed blaze. (Record, pine)  
and remains of the BTs mkd. by Byron, in 1958, and reported by Bedell, Rogers, and Peterson  
A decayed snag, 11" dia., species indeterminate, bears N.73°E., 29.0 ft., with healed blaze. (Record, fir)  
A fir, 19" dia., bears S.30°E., 10.6 ft., with healed double blaze.  
A dead chinquapin, 11" dia., bears S.43°W., 35.6 ft., with decayed blaze. continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, T30-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole, bears N.89°W., 9.2 ft., with fallen trunk, size & species indeterminate, lying alongside, no marks visible. (Record, fir)  
and BT mkd. by Tracy, in 1964, and reported by Bedell, Rogers, and Peterson  
A fir, 19" dia., bears N.71°W., 54.8 ft., with healed double blaze.  
and bearing tree mkd. by Bedell, Rogers, and Peterson  
A fir, 8" dia., bears N.22°W., 14.5 ft., with healed blaze.  
and new bearing tree  
A fir, 10" dia. bears N.33°E. 28.0 ft. mkd. T30S R8W S7 BT  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

DCS0-GIS Corner visitation - 4/24/2007 - Typed: 2/9/2011 - C.S. File 67/33-1: Fd-2½" BC - 0k; 3 live BTs, 1 snag

Daniel A Renton, Minister-Glaeser Surveying - August Karlsen & Crew - For: US Department of Interior, BLM Beetle Battle North-Task C -May 17, 2023 - M178-73 A-D

-----  
Found - 2½" County Surveyors Office brass cap (properly mkd) on pipe 15" above ground from which:  
A post with BLM boundary sign bears North 6 ft.  
A 20" Fir bears N.73°W., 54.6 ft with healed blaze & BT sign (1964)  
An 18" stump bears N.17°W., 19.8 ft. with scribe remains "BT" (1855)  
A 10" Fir bears N.26°W., 14.4 ft with healed blaze and BT signs (1986)  
A 26" Fir bears S.34°E., 10.4 ft with healed blaze & BT signs (1958)  
An 11" Chinquapin bears S.42°W., 35.1 ft with partial healed blaze & BT signs (1958)  
An 18" rotted stump bears N.49°E., 33.1 ft. (1855)  
A stump, size and species indeterminate, bears S.47°E., 76.5 ft. (1855)  
A mound of wood debris bears N.89°W., 9.2 ft. (only remaining evidence) (1958)  
New - A 16" Fir bears S.33°W. 31.0 ft mkd "T30S R9W S13 BT"  
A 15" Fir bears N.52°E., 64.6 ft mkd "T30S R8W S7 BT"  
Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs  
Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT.