

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 100170

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T31-1W

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7493-94)

-----  
Set a basalt stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which  
A Fir 30" dia., bears N.37°E., 49 lks. dist. mkd. ¼ S31 BT  
A Fir 30" dia., bears S.55°W., 33 lks. dist. mkd. ¼ S36 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7505)

-----  
The ¼ sec. cor. established for secs. 31 and 36, which is a basalt stone, firmly set, 4x10x6 ins. above ground, mkd. ¼ on W. face, from which  
A Fir 30" dia., bears N.37°E., 49 lks. dist. mkd. ¼ S31 BT. (Old BT)  
A Fir 30" dia., bears S.55°W., 33 lks. dist. mkd. ¼ S36 BT. (Old BT)  
I now change this cor. to refer to sec. 36 only, and obliterate the marks on the bearing tree referring to S.31. Re-mark the stone ¼ S36 on W. face, from which  
A Fir 10" dia., bears N.87°W., 36 lks. dist. mkd. ¼ S36 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-56

-----  
Found - Stone at ¼ corner, faint "¼".  
Orig. 30" now 36" D.Fir, S.55°W., 21.8 ft., shows good scar.  
10" now 13" W.Fir, N.87°W., 23.8 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
1 S 36 | 1  
W ¼ | E  
1968

All BTs. OK and tagged.