

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7506)

Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 30 and 31 only, with brass cap marked:

T31S	T31S
R1W	<u>S 30</u>
	S 31
S36	R1E
	1923

from which

A Fir 28" dia., bears N.59°E., 102 lks. dist. mkd. T31S R1E S30 BT.

A Fir 8" dia., bears S.59°E., 81 lks. dist. mkd. T31S R1E S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-57

Found - 28" now 34" D.Fir N.59°E., 67.3 ft. shows good scar
8" now 10" W.Fir S.59°E., 53.5 ft., shows good scar
GLO brass cap at corner, properly mkd. in 1923.
New BT - 34" D.Fir N.5°W., 28.2 ft. scribed T31S R1W S36 CSBT