

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30, only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7508)

-----  
Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 19 & 30 only, with brass cap marked:

|      |             |
|------|-------------|
| T31S | T31S        |
| R1W  | <u>S 19</u> |
| S25  | S 30        |
|      | R1E         |
|      | 1923        |

from which

A Hemlock 24" dia., bears N.35°E., 41 lks. dist. mkd. T31S R1E S19 BT.

A Yew 12" dia., bears S.58°E., 20 lks. dist. mkd. T31S R1E S30 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-50

-----  
Found - GLO brass cap, properly mkd. in 1923.  
12" Yew now 12", S.58°E., 13.2 ft. scribe visible  
24" now 27" Hemlock, N.35°E., 27.1 ft., shows good scar.

New BT - 9" Yew, N.44°W., 28.0 ft. scribed T31S R1W S25 CS BT.