

TOWNSHIP 31 RANGE 01e POINT IDENTIFIER # 100630

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (East) T31-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7500)

Set a basalt stone 15x12x8 ins., 10" in the ground for cor. of secs. 1 and 12, mkd. with 1 notch on N. and 5 notches on S. edges, from which
A Fir 12" dia., bears S.19°W., 32 lks. dist. mkd. T31S R1W S12 BT.
A Fir 30" dia., bears N.40°W., 41 lks. dist. mkd. T31S R1W S1 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7514)

The cor. of secs. 1 and 12 only, which is a basalt stone, firmly set, 5x12x8 ins. above ground mkd. with 1 notch on N. and 5 notches on S. edges; from which
A Fir 12" dia., bears S.19°W., 32 lks. dist. mkd. T31S R1W S12 BT. (Old BT)
A Fir 30" dia., bears N.40°W., 41 lks. dist. mkd. T31S R1W S1 BT. (Old BT)
Re-mark the stone S12 on SW. and S1 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 16, 1968 - C.S. File 54/71

Found - 5x12x8 stone at sec. cor. marked with notches.
30" D.Fir now snag, N.40°W., 27.1 ft. shows good scar.
12" now 14" D.Fir S.19°W., 21.1 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
R T 31 S R
1 S 1 | S 6 1
W S 12 | E
1968

New BTs- 10" D.Fir N.53°W., 59.0 ft. mkd. T31S R1W S1 CS BT.
14" D.Fir N.22°E., 5.9 ft. mkd. T31S R1E S6 CS BT.