

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. of Sec. 1 only, T31-1W

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7500)

 Set a basalt stone 15x12x6 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
 A Fir 50" dia., bears N.70°E., 22 lks. dist. mkd. ¼ S6 BT
 A Fir 24" dia., bears S.30°W., 79 lks. dist. mkd. ¼ S1 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7515)

 The ¼ sec. cor., established for secs. 1 and 6, which is a basalt stone, firmly set, 5x12x6 ins. above ground mkd. ¼ on W. face; from which
 A Fir 50" dia., bears N.70°E., 22 lks. dist. mkd. ¼ S6 BT. (Old BT)
 A Fir 24" dia., bears S.30°W., 79 lks. dist. mkd. ¼ S1 BT. (Old BT)
 I now change this cor. to refer to sec. 1 only, and obliterate the marks on the bearing tree referring to sec. 6. Re-mark the stone ¼ S1 on W. face; from which
 A Fir 64" dia., bears N.40°W., 19 lks. dist. mkd. ¼ S1 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-83

 Found - No trace of corner stone nor SW. orig. BT.
 Orig. 50" Fir now 54" sawed stump, N.70°E., 14.5 ft., shows good scar.
 64" now 66" Fir sawed stump, N.40°W., 12.5 ft., open and find scribe. (1923 BT)

Set Brass cap at cor. mkd: County Surveyors Office

| | | |
|---|--------|---|
| R | T 31 S | R |
| 1 | ¼ S 1 | 1 |
| W | 1968 | E |

No live trees or suitable stumps close for bearing trees.
 Bearing Objects:
 5/8" Iron rod 10 ft. South of ¼ corner.
 5/8" Iron rod 15 ft. South of ¼ corner.
 Cor. lies approx. 100 ft. N. of ridge top, course E. and W. on moderate North slope.