

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW S. 6, T31-1E; SW Cor. S31, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7515)

Set an Iron post 3 ft. long, 3" dia., 28" in the ground for cor. of Tps. 30 and 31 S., R 1 E., only with brass cap marked:

T31S	T30S
R1W	R1E
	<u>S 31</u>
S 1	S 6
	T31S
	1923

from which

A B.Oak 7" dia., bears N.84°E., 60 lks. dist. mkd. T30S R1E S31 BT.

A Madrona 16" dia., bears S.72°E., 34 lks. dist. mkd. T31S R1E S6 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-84

Found - After diligent search, we find 3" I.P. and brass cap approx. 40 ft. down hillside, out of ground.

Reset brass cap in mound of stone at corner point.

Found - Orig. 7" now 8" B.Oak, N.84°E., 39.6 ft., now 7 ft. high snag. We open and find scribing.

Orig. 16" now 17" Madrona, down and out of position, S.72°E., 22.4 ft. scribe visible on underside.

New BT - 8" D.Fir S.83½°W., 64.6 ft. mkd. T31S R1W S1 CS BT.

No other live trees or stumps close for bearing trees.

Set 5/8" Iron rod, 20 ft. North and 5/8" I.Rod 25 ft. North of corner.

Cor. lies on steep westerly slope approx. 635 ft. North of the E. ¼ corner to sec. 1, T31-1W.