

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11224)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T31S	R1E
S 19	S 20
S 30	S 31
1923	

from which

- A fir, 40" dia., bears N.65°E., 26 lks., mkd: T31S R1E S20  
BT.
- A fir, 52" dia., bears S.20°E., 82 lks., mkd: T31S R1E S29  
BT.
- A fir, 40" dia., bears S.23°W., 56 lks., mkd: T31S R1E S30  
BT.
- A fir, 42" dia., bears N.30°W., 45 lks., mkd: T31S R1E S19  
BT.