

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6; 31, 32 T30-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11197)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd

T30S	R1E
S 31	S 32
S 6	S 5
T31S	
1923	

from which

- A cedar, 36" dia., bears N.86°E., 251 lks., mkd: T30S R1E S32 BT.
- A cedar, 28" dia., bears S.21°E., 44 lks., mkd: T31S R1E S5 BT.
- A for, 48" dia., bears S.78°W., 110 lks., mkd: T31S R1E S6 BT.
- A fir, 40" dia., bears N.82°W., 162 lks., mkd: T30S R1E S31 BT.