

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11215)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T31S	R1E
S 8	S 9
S 17	S 16
1923	

from which

- A fir, 36" dia., bears N.77°E., 48 lks., mkd: T31S R1E S9 BT.
- A fir, 28" dia., bears S.15°E., 40 lks., mkd: T31S R1E S16 BT.
- A hemlock, 10" dia., bears S.45°W., 40 lks., mkd: T31S R1E S17 BT.
- A fir, 30" dia., bears N.57°W., 39 lks., mkd: T31S R1E S8 BT.