

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11218-9)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S}{S}$   
          4  
          9  
          1923

from which

A fir, 34" dia., bears N.68°W., 11 lks., mkd: 1/4 S4 BT.

A fir, 7" dia., bears S.67°W., 24 lks., mkd: 1/4 S9 BT.

-----  
Jim Landrum, USFS & Dep. Co. Surveyor - Leonard Herzstein - May 18, 1983 - C.S. File 62/10-17

-----  
Found - 1923 GLO brass cap, properly mkd., on 1" dia. iron post, firmly set, projecting 3" above a 2 ft. mound of stone.

Orig. fir snag, size indeterminate, N.68°W., 7.3 ft. with no marks visible.

New BTs- 13" cedar, N.73°E., 30.0 ft. scribed "1/4 S4 CS BT" on a single blaze.

16" W. fir, S.35°W., 26.7 ft. scribed "1/4 S9 CS BT" on a single blaze.

Note - From the Junction of USFS Rd. #'s 2925-700 and 2925, proceed up Rd. #2925-800, 0.6 miles to location tag on 36" fir, then go south approx. 3 chains to corner.