

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11200-1)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T31S R1E  
S 21|S 22  
S 28|S 27  
1923

from which

- A chinquapin, 8" dia., bears N.70°E., 9 lks., mkd: T31S R1E S22 BT.
- A fir, 10" dia., bears S.70°E., 34 lks., mkd: T31S R1E S27 BT.
- A fir, 40" dia., bears S.79°W., 29 lks., mkd: T31S R1E S28 BT.
- A chinquapin, 10" dia., bears N.39°W., 16 lks., mkd: T31S R1E S21 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17631)

-----  
The cor. of secs. 21, 22, 27, & 28, which is an iron post, 2" dia., 10" above ground, firmly set, mkd. & witnessed as described in the official record.