

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11202)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

T31S R1E
S 16|S 15
S 21|S 22
1923

from which

- A cedar, 32" dia., bears N.30°E., 46 lks., mkd: T31S R1E S15 BT.
- A fir, 4" dia., bears S.37°E., 14 lks., mkd: T31S R1E S22 BT.
- A cedar, 34" dia., bears S.80°W., 74 lks., mkd: T31S R1E S21 BT.
- A cedar, 30" dia., bears N.49°W., 18 lks., mkd: T31S R1E S16 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17632)

The cor. of secs. 15, 16, 21, & 22, which is an iron post, 2" dia., 10" dia., above ground, firmly set, mkd. and witnessed as described as described in the official record.