

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11204-5)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 9 | S 10  
1923

from which

A fir, 60" dia., bears N.36°E., 137 lks., mkd: 1/4 S10 BT.

A cedar, 48" dia., bears N.75°W., 90 lks., mkd: 1/4 S9 BT.  
1/4 Sec. cor. is in swampy draw, opening NW

-----  
GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17633)

-----  
The 1/4 sec. cor. of secs. 9 & 10, which is an iron post, 1" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.

The 1/4 sec. cor. is in a small swampy draw, draining NW.