

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1, 2, 11, & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17659)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T31S R1E
S 2 | S 1
S 11 | S 12
1936

from which

- A W.Fir, 9" dia., bears N.3°E., 126 lks., mkd: T31S R1E S1 BT.
- A fir, 10" dia., bears S.78°E., 38 lks., mkd: T31S R1E S12 BT.
- A fir, 37" dia., bears S.43°W., 154 lks., mkd: T31S R1E S11 BT.
- A fir, 7" dia., bears N.87°W., 71 lks., mkd: T31S R1E S2 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - July 10, 1985 - C.S. File 62/28-14

Found - A 2½" dia. GLO disk, properly mkd, on a 2" dia. galvanized iron pipe firmly set and protruding 8" from ground. (1936)

A W.Fir, 9" dia., now an 18" DBH Noble Fir, with a fully healed single blaze, bears N.03°E., 80.6 ft. (Record N.03°E., 83.2 ft. (This is a slope dist.) Orig.

A fir, 10" dia., now an 18" DBH Noble Fir, with a fully healed single blaze, bears S.78°E., 25.1 ft. dist. (As per orig. record)

A fir 37" dia., now a 47" DBH Noble Fir with a fully healed single blaze, bears S.43°W., 101.0 ft. dist. (Orig. rec S.43°W., 101.6 ft. dist. (This is a slope dist.)

A fir, 7" dia., now an 18" dia., 2 ft. high shattered and rotted fir stump with evidence of a blaze, but no scribing. Bears N.87°W., 46.9 ft. dist. (As per orig. rec.)

Set - Monument position accepted. Monument does not appear disturbed and distances to SE and NW bearing trees, which are readily measured level, match trig, record.

New - A 10" DBH Noble Fir, scribed T31S R1E S2 CS BT on, a double blaze, bears N.78¾°W., 22.5 ft.

continued next page

TOWNSHIP 31 RANGE 01E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A USC & GS bench mark which is a disk, stamped Z501 1949, set in a concrete post 1 ft. in dia., and protruding 8" above ground bears S.78½°E., 220.1 ft. dist.
Corner is located near top of divide, approx. 2 miles west from Huckleberry Lake.