

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 18 only, T31-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11163)

Set a stone for cor. of secs. 12, 13, 7, & 18, 16x12x12", 12" in the ground, mkd with 2 notches on N & 4 notches on S edge, from which

- A R.Fir, 24" dia., bears N.56°E., 23 lks., mkd: T31S R2E S7 BT.
- A R.Fir, 36" dia., bears N.66°W., 77 lks., mkd: T31S R1E S12 BT.
- A chinquapin, 10" dia., bears S.72°E., 46 lks., mkd: T31S R2E S18 BT.
- A R.Fir, 36" dia., bears S.49°W., 120 lks., mkd: T31S R1E S13 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17625-6)

The old cor. of secs. 7, 12, 13, & 18, which is a lava stone, 16x12x12", firmly set.

I change this cor. to refer to secs. 7 & 18 only.

At point for cor.

Set an iron post, 27" long, 2" dia., 20" in the ground, to bedrock, and in a mound of stone to top, for cor. of secs. 7 & 18 only, with brass cap marked:

T31S		T31S
		S 7
R1E		S 18
S 12		R2E
1936		

from which

- A fir, 40" dia., bears N.56°E., 23 lks., blaze healed; I do not open. I reblaze & re-mark this tree T31S R2E S7 BT (Old BT)
- A fir snag, 30" dia., bears S.50°W., 124 lks., mkd. T31S R1E S13. I obliterate the marks. (OBT)
- A fir snag, 40" dia., bears N.66°W., 83 lks., mkd. T31S R1E S12 BT. I obliterate the marks. (Old BT)
- A pine, 6" dia., bears S.75½°E., 133 lks., mkd T31S R2E S18 BT. (New BT)