

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6 only

Alias	Description

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11165)

Set a fir stake, 3½" sq. and 4 ft. long, 24" in the ground, for ¼ sec. Cor., marked ¼ S on W side; from which

 A R.Fir, 16" dia., bears N.66°E., 25 lks., mkd: ¼ S BT.

 A R.Fir, 16" dia., bears N.75°W., 38 lks., mkd: ¼ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17628-9)

The old ¼ sec. cor. of secs. 1 & 6, which is a fir post, 24x3x3" above ground, mkd: ¼ S on W face.

I change this cor. to refer to sec. 6 only

At point for cor.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 6 only, with brass cap marked

| ¼ S6
1936

from which

 A fir, 28" dia., bears N.66°E., 26 lks., blaze healed; I do not open. I reblaze and re-mark this tree ¼ S6 BT (Old BT)

 A fir, 27" dia., bears N.76°W., 40 lks., mkd. ¼ S BT. I obliterate the marks (Old BT)

 A W.Pine, 42" dia., bears S.42°E., 34 lks., mkd. ¼ S6 BT. (New BT)