

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T31-2

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7459)

-----  
Set post cor. secs. 30, 31, 25 and 36, from which  
A Fir 18" dia., bears N.64°W., 11 lks. dist.  
A Fir 18" dia., bears S.50°W., 16 lks. dist.  
A Fir 18" dia., bears S.72°E., 23 lks. dist.  
A Cedar 20" dia., bears N.5°E., 9 lks. dist.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7502)

-----  
This cor. is nearly obliterated. The only remaining traces being two of the bearing trees, deeply overgrown.  
I re-establish the cor. in its original position as follows:  
Set an ironstone 15x10x6 ins., 10" in the ground, for cor. of secs. 25, 30, 31 and 36, mkd. with 5 notches on N. and 1 notch on S. edge, from which  
A Cedar 28" dia., bears N.5°E., 9 lks. dist. mkd. T31S R1W S30 BT. (Old BT)  
A Madrone 10" dia., bears S.45½°E., 57 lks. dist., mkd. T31S R1W S31 BT.  
A Fir 20" dia., bears S.8°W., 70 lks. dist. mkd. T31S R2W S36 BT.  
A Yellow Pine 16" dia., bears N.22°W., 34 lks. dist. mkd. T31S R2W S25 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 (DCSO records Vol. 18 Page(s) 7583)

-----  
The Sec. Cor., which is an ironstone, firmly set, 5x10x6 ins., above ground, mkd. with 5 notches on N. and 1 notch on S. edges, from which  
A Cedar 28" dia., bears N.5°E., 9 lks. dist. mkd. T31S R1W S30 BT. (Old BT)  
A Yellow Pine 16" dia., bears N.22°W., 34 lks. dist. mkd. T31S R2W S25 BT (Old BT)  
(The old bearing trees in secs. 31 and 36 are dead and fallen.)  
A Yellow Pine 30" dia., bears S.66°E., 132 lks. dist. mkd. T31S R1W S31 BT. (New BT)  
A Laurel 14" dia., bears S.74½°W., 148 lks. dist. mkd. T31S R2W S36 BT. (New BT)

(Cont. Next Page)

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - John M. Powell, Frank Jones,  
& Terry Connell, crew - July 1966 - C.S. File 54/28-43

-----  
Found - Stone at sec. corner, no marks visible.  
Orig. 28" Cedar N.5°E., 5.9 ft., scribe visible "31S  
R1W S30".  
16" Pine now snag, N.22°W., 22.4 ft., scribe visible  
"R2 S25 BT"  
30" Pine S.66°E., 87.1 ft., scribe visible "R S",  
pitched over.  
14" Laurel now 19", S.74½°W., 97.7 ft., scribe  
visible "36 BT"

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
2 S 25 | S 30 1  
W S 36 | S 31 W  
1966

New BTs- 6" D.Fir S.41°W., 7.5 ft. scribed T31S R2W S36 CS BT  
7" Laurel N.66°W., 22.6 ft. scribed T31S R2W S25 CS  
BT.

This corner lies West of trail, tag on Pine tree, N.66°W.  
87.1 ft. to section corner.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173-2