

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7458)

-----  
 Set post, cor. secs. 19, 30, 24 and 25, from which  
 A Fir 18" dia., bears N.5°E., 20 lks. dist.  
 A Fir 20" dia., bears N.60°W., 6 lks. dist.  
 A Fir 18" dia., bears S.50°W., 33 lks. dist.  
 A Fir 18" dia., bears S.89½°E., 138 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 (DCSO records Vol. 18 Page(s) 7584-85)

-----  
 The cor. of secs. 19, 24, 25 and 30, located by reference to the SE. bearing tree; no other evidence.  
 At exact cor. point  
 Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd:

T31S	
R2W	R1W
<u>S24</u>	<u>S19</u>
S25	S30
1923	

from which  
 A Fir 18" dia., bears S.89½°E., 138 lks. dist. mkd. T31S R1W S30 BT. (Old BT)  
 (The old bearing trees in secs. 19, 24 and 25 are dead and down.)  
 A Cedar 22" dia., bears N.65°E., 83 lks. dist. mkd. T31S R1W S19 BT (New BT)  
 A Fir 5" dia., bears S.50°W., 45 lks. dist. mkd. T31S R2W S25 BT. (New BT)  
 A Fir 5" dia., bears N.75°W., 14 lks. dist. mkd. T31S R2W S24 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones; Terry Connell, crew - July 1966 - C.S. File 54/28-41

-----  
 Found - GLO brass cap mkd. incorrectly: S25 | S30  
S36 | S31 1922

This cap 1 mile too far north  
 Orig. 18" D.Fir, now snag, N.5°E., 13.2 ft., opened for scribe :BT".  
 Orig. 20" D.Fir, now down, N.60°W., 4.0 ft., opened for scribe "BT".  
 Orig. 18" D.Fir, now 27", S.89½°E., 91.1 ft., shows scar. (Rescribed)

(Cont. Next Page)

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. 18" D.Fir, now stump, S.50°W., 21.8 ft. (dist. should be 17.3 ft.) No scribing on stump, but part of old burned face.  
11" D.Fir N.79°W., 9.4 ft., opened for scribe "R2W"  
13" D.Fir S.49°W., 30.3 ft., shows good scar. (1922)  
27" D.Fir S.89½°E., 91.1 ft., rescribed on bark "T30S R1W S30". (1922)  
Set brass cap alongside 1922 brass cap and marked:  
County Surveyors Office  
R T 31 S R  
2 S 24 S 19 1  
W S 25 S 30 W  
1966  
New BTs- 12" D.Fir S.76°E., 9.5 ft. scribed T31S R1W S30 CSBT  
11" D.Fir N.19°E., 27.9 ft. scribed T31S R1W S19 CSBT.  
10" D.Fir N.67°W., 23.4 ft. scribed T31S R2W S24 CSBT.  
11" D.Fir S.42°W., 18.7 ft. scribed T31S R2W S25 CSBT.  
Fd. OK, July 7, 1981 by L. Herzstein - C.S. File 61/27-9