

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7458)

Marked a Fir 30" dia. for 1/4 sec. cor., from which
A Fir 18" dia., bears N.74°W., 31 lks. dist.
A Fir 30" dia., bears N.10°E., 46 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones; Terry Connell, crew - June/July 1966 - C.S. File 54/28-40

Found - 30" Corner tree, now dead snag.
18" D.Fir, now stump, N.74°W., 20.5 ft., bark scribed "1/4S".
30" D.Fir, now dead snag, N.10°E., 30.4 ft., shows good scar. Opened tree for scribe "BT". Find dist. to be 34.0 ft.

Set brass cap South side corner tree, mkd. R T 31 S R
1/4 2 S 24 | S 19 1
W 1966 W

New BTs- 9" W.Fir N.29°W., 34.6 ft. scribed 1/4 S24 CS BT.
12" W.Fir S.59°E., 13.0 ft. scribed 1/4 S19 CS BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 4, 1993 - C.S. File 64/47-12

Found - 30" now 42" dia., 30 ft. high D.Fir snag with single healed blazes on east and west side of corner tree (orig. cor. tree).
2 1/2" dia. DCSO Brass Cap on 1 1/4" O.D. by 36" long I.P. is fd. out of ground along south side of corner tree County Surveyors Office

R 1/4 R
2 S24 | S19 1
W T 31 S W
1966

Brg's & distances taken from center of Orig. Cor. tree
18" now 30" dia. 5' high D.Fir stump with fully healed single blaze & bark scribing "1/4S" bears N.77 1/2°W., 21.5 ft. (rec. N.74°W., 20.5 ft. dist is a possible face to face measurement) Orig. BT.
30" now 42" dia. 15' high D.Fir snag with a previously opened blaze, scribing visible "BT" bears N.10°E., 34 ft. (orig. rec. N.10°E., 30.4 ft.) Orig BT.

Brg's & Dist. taken from reset position of 1966
(Cont. Next Page)

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

9" now 12" dia. 1½ ft. high rotted W.Fir stump scribing fd. "BT" bears N.27°W., 34.2 ft. (rec. N.29°W., 34.6 ft. distance is a possible slope dist.

12" now 21" dia. W.Fir with a fully healed double blaze bears S.61°E., 12.7 ft. (rec. S.59°E., 13 ft.)

We investigated numerous positions to reset 1966 BC/IP. None of which fit well on ground (BC/IP would fall inside cor. tree or lie on top of large undisturbed roots) We reset DCS0 BC/IP at most probable 1966 position between two large roots on southerly side of corner tree. Loose dirt was found between roots down to a depth that ground marks showed on BC/IP. BC/IP protrudes 18" above ground and is surrounded by a 2½" ft. dia., 15" high mound of stone.

County Surveyor Office
N15E ¼ 2.6ft
R to cor R
2 S24|S19 1
W Reset 1993 W
T31S
1966

New Accessories: (BRG's & Dist. taken from center of orig. cor. tree)

DCS0 BC/IP bears S.15°W., 2.6 ft.

21" dia. W.Fir (1966 ren tree) with a fully healed double blaze bears S.49½°E., 13 ft.

6" dia., W.Fir, double blazed and scribed "¼ S19 CS BT" bears S.14½°E., 20.2 ft.

8" dia., D.Fir, double blazed and scribed "¼ S24 CS BT" bears S.79°W., 12.9 ft.

8" dia., Maple, double blazed and scribed "¼ S19 CS BT" bears N.19°E., 19.5 ft.

The corner is the Orig. corner tree. All new accessories are in reference to the corner tree. The DCS0 BC/IP should be used as a reference to the corner tree.

Fd. OK, May 1994 by R. Brown - Land partition 1994-0036
Fd. OK 3/2023 by R.Brown, M182-14