

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7458)

-----  
Set post, cor. secs. 13, 24, 18 and 19, from which  
An Ash 18" dia., bears N.77°W., 114 lks. dist.  
An Ash 18" dia., bears S.1°E., 300 lks. dist.  
A Pine 18" dia., bears N.40°E., 82 lks. dist.  
A Pine 15" dia., bears S.30°W., 150 lks. dist.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit:  
N.E. Richardson; B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38

-----  
Position identified from Orig. BT:  
Oak N.77°W., 114 lks.  
Stump of Pine, N.40°E., 82 lks.  
(Original notes call for 2 Ash BTs. One is Oak mentioned above and other must have been an Oak as there has never been Ash on spur.)  
Set rock 6" x 10" x 18", 16" in ground for corner, from which  
A 14" B.Oak N.42°E., 131 lks. "T31S R1W S18 CS BT".  
A 20" B.Oak N.65½°W., 67 lks. "T31S R2W S13 CS BT".  
A 20" Madrona S.56°W., 27 lks. "T31S R2W S24 CS BT".  
An 18" Fir S.10°E., 150 lks. "T31S R1W S19 CS BT".

Douglas Co. Surveyors Office - John M. Powell, Frank Jones;  
Terry Connell, crew - July 1966 - C.S. File 54/28-39

-----  
Found - Stone at section corner, 16x10x8.  
20" B.Oak N.65½°W., 44.2 ft. Opened for scribe "3BT". Rotten. (Brg. should be N.75½°W.)  
No trace of NE. or SE. BTs.  
20" Laurel now 24", S.56°W., 17.8 ft., no scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
2 S 13 | S 18 1  
W S 24 | S 19 W  
1966

New BTs- 24" Cedar N.45½°W., 11.9 ft. scribed T31S R2W S13 CS BT.  
14" D.Fir N.2½°W., 22.9 ft. scribed T31S R2W  
10" D.Fir S.45°E., 39.4 ft. scribed T31S R1W S19 CS BT.

Reblazed and rescribed:  
24" Laurel S.56°W., 17.8 ft. scribed T31S R2W S24 CS BT.