

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7457)

-----  
Set post cor. secs. 6, 7, 1 and 12, from which  
An Oak 10" dia., bears N.14°W., 100 lks. dist.  
An Oak 12" dia., bears N.28°E., 36 lks. dist.  
An Oak 9" dia., bears S.18°W., 79 lks. dist.  
A Pine 24" dia., bears S.68°E., 49 lks. dist.

Survey by Glenn S. Baughman - For: Tiller Ranger Dist. - June 20, 1967 - C.S. File 55/41-6 and M 34-23

-----  
Set 2½" bronze disk, set by single proportionate method, from which  
8" D.Fir bears N.14°30'E., 51.7 ft. scribed T31S R1W S6 BT.  
10" D.Fir bears S.86°E., 35.6 ft. mkd. T31S R1W S7 BT.  
16" Sugar Pine bears N.54°W., 1.7 ft. scribed T31-2W S1 BT  
10" Cedar bears S.34°30'W., 15.9 ft. scribed T31S R2W S12 BT.

BLM dependent resurvey by Leonard E. Herzstein, Land Surveyor (U.S. Forest Service) - under Group #2013, surveyed May 2002/Feb. 2003 - (DCSO records Vol. 54 Page(s) 20780-1)

-----  
The cor. of secs. 1, 6, 7, & 12, reestablished by proportionate measurement by Baughman, in 1967. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2" dia. iron post, firmly set, projecting 14" above the ground, with brass cap (properly) mkd.

from which remains of bearing trees mkd. by Baughman in 1967  
A D.Fir snag, 12" dia., bears N.10¼°E., 51.0 ft., with healed blaze.  
A D.Fir snag, 13" dia., bears S.88¾°E., 35.9 ft., with healed blaze.  
An I.Cedar, 17" dia., bears S.33¼°W., 15.9 ft., with healed blaze.  
A Ponderosa pine, 20" dia., bears N.36¼°W., 1.9 ft., with healed blaze.

and new bearing trees  
A ponderosa pine, 6" dia., bears N.59¾°E., 111.2ft., mkd. X BT.  
A B.Oak, 9" dia., bears S.59¼°E., 31.3 ft., mkd. T31S R1W S7 BT.

Corner point lies North, 6.0 ft. of barbed wire fence corner, fences bear N., E. and W.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T31-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

From this point, the National Geodetic Survey B-Order geodetic station "DREW" bears S.0°19'41"W. (mean bearing), 11709.80 ft. (sea level), monumented with a standard NGS brass tablet, 3½" dia., firmly set in a concrete cylinder, 8 ins. in dia., mkd. DREW.

From this same point, a 1" dia. iron rod, loosely set, projecting 9" above ground, established by person(s) unknown, bears S.50°35'E., 126.59 ft.

from which trees mkd. by person(s) unknown

An incense cedar, 27" dia., bears N.8½°E., 25.4 ft., with healed blaze.

A D.Fir, 14" dia., bears S.54°E., 31.3 ft., with healed blaze.

A D.Fir, 12" dia., bears S.46°W., 41.2 ft., with healed blaze.

A D.Fir, 17" dia., bears N.39½°W., 18.0 ft., with healed blaze.

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hellman & Jacob Hunt - 8/15/2016 - C.S. File 65/93-39

Found - 2½" galvanized iron pipe with a 2½" brass cap, projecting 10" above a mound

No trace of a (10" Oak) 1857, (N.14°W., 66.0 ft)1857

No trace of a (12" Oak) 1857, (N.28°E., 23.8 ft)1857

No trace of a (9" Oak) 1857, (S.18°W., 52.1 ft)1857

No trace of a (24" Pine) 1857 (S.68°E., 32.3 ft)1857

A 12" fir snag with scribe visible on a rotted face, (N.14°30'E., 51.7')1967, (N.10°15'E., 51.0')2003

A 12" fir snag with a healed single blaze, (S.86°E., 35.6')1967, (S.88°45'E., 35.9')2003

A 26" pine with a healed single blaze, (N.54°W., 1.7')1967, (N.36°15'W., 1.9')2003

A 21" cedar with a healed single blaze, (S.34°30'W., 15.9 ft.)1967, (S.33°15'W.)2003

A 15" pine with a healed double blaze, (N.59°45'E., 111.2 ft)2003

A 11" oak with a healed single blaze, (S.59°30'E., 31.3 ft)2003

A 1" iron rod by persons unknown, projecting 8" above the ground. (S.50°35'E., 126.59 ft)2003

No new accessories added.

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.

Latitude: N.42°54'06.576" Longitude: W.122°52'58.962"

Datum: NAD83 Source: post processed resource grade, as reported by Jack Snyder.