

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW. Cor. Sec. 6 (NW Tsp. Cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6754)

-----  
A Fir 15" dia., cor. Ts. 30 & 31., R. 1 & 2 W., from which  
A Fir 18" dia., bears S.70°W., 28 lks.  
A Fir 15" dia., bears N.66°W., 121 lks.  
A Fir 48" dia., bears N.48°E., 30 lks.  
A Fir 15" dia., bears S.40°E., 20 lks.

Douglas Co. Surveyors Office - John M. Powell & crew - June 6, 1966 - C.S. File 54/28-7

-----  
Found - 15" Fir, now 36" Corner Tree, had been opened, scribing.  
18" Fir now stump, S.70°W., 18.5 ft., shows good scar.  
15" Fir now stump, N.66°W., 79.9 ft., shows scar.  
48" Fir now 49" N.48°E., 19.8 ft., very old bark scribe.  
15" Fir now 34" S.40°E., 13.2 ft., shows good scar  
Set Brass cap at cor. mkd: County Surveyors Office

R	T30S		R	
2	S 36		S 31	1
W	S 1		S 6	W
1966				

Brass cap set at NW. side of corner tree.  
New BTs- 12" D.Fir N.19°W., 81.3 ft. scribed T30S R2W S36 CS BT.  
11" D.Fir S.12°W., 109.3 ft. scribed T31S R2W S1 CS BT.  
Corner lies on top of main ridge, running E. and W.