

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Glenn Baughman - For: Umpqua Nat'l Forest, Tiller Ranger
Dist. - June 20, 1967 - C.S. 55/41 & M34-23

Set - 2½" bronze disk by single proper. method, from which
14" D.Fir bears N.63°E., 52.5 ft., scribed W1/16 S6 BT.
24" Oak bears S.23°E., 71.0 ft., scribed W1/16 S7 BT.

Wm. Ruppert - For: USFS - Dec. 1977 - M65-60

Found - 2"x36" pipe with brass cap lying on top of ground.
14" D.Fir, scribing visible.
28" B.Oak, scribing visible.
Reset pipe & brass cap fd laying on ground at rec. distances
from BTs:
14" D.Fir N.59°40'E., 52.5'
28" B.Oak S.25°10'E., 71.0'

BLM dependent resurvey by Leonard E. Herzstein, LS USFS,
under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO
records Vol. 54 page(s) 20787-8

The W 1/16 sec. cor. of secs. 6 & 7 established by Baughman,
in 1967, and perpetuated by Ruppert, in 1977, and accepted as
the corner; monumented with a 2" dia. iron post, firmly set,
projecting 7" above ground and in a collar of stones, with
brass cap (properly) mkd.
from which bearing trees mkd. by Baughman in 1967
A D.Fir, 22" dia., bears N.60°E., 52.0 ft., with healed
blaze.
A B.Oak, 32" dia., bears S.25¼°E., 70.6 ft., with scribe
marks W1/16 S7 B visible on partially healed blaze.
Corner point lies S.70°E., 7.6 ft, of barbed wire fence
corner, fences bear N.70°E. and W.

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hellman &
Jacob Hunt - 8/15/2016 - C.S. File 65/93-49

Found - A 2½" galvanized iron pipe with a 2½" brass cap,
projecting 6" above half of a mound of stone to
the SW. Recent earth work to the east of the
corner has disturbed the mound of stone but the
corner monument remains solid. (properly mkd)
A 27" fir with a healed single blaze, (N.63°E.,
52.5 ft) 1967
A 34" oak with a healed single blaze, (S.23°E.,
71.0 ft) 1967
No new accessories added.
continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 120600

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 6 & 7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.
Lat: N.42°54'06.802" Long: W.122°52'52.957"
Datum: NAD83