

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7473

Set ¼ sec. post, from which
A laurel, 12" dia., bears N.88°E., 20 lks.
A cedar, 24" dia., bears S.80°E., 20 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7586-7)

Proportional measurement
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked

¼ $\frac{S\ 19}{S\ 30}$
1923

from which
A fir, 16" dia., bears N.10°E., 8 lks., mkd: ¼ S19 BT.
A cedar, 24" dia., bears S.60°E., 25 lks., mkd: ¼ S30 BT.

Fd. Ok by DCSO JMP, 9/1968 - Fd. 1923 BC firmly in place & Both BTs - C.S. File 54/71-64A

Leonard Herzstein, USFS & Deputy Douglas Co. Surveyor - Witness, Jim Landrum - Feb. 1982 - C.S. File 61/32-7

CONDITION REPORT ONLY
Found - 1922 GLO brass cap marked US Gen. Land Office ¼ S19 S30 1922. (GLO notes says 1923) Firmly set projecting 8" above ground. I.P. is leanly slightly westerly with brass cap cocked to the west slightly more.

18" D.Fir, N.10°E., 5.3 ft. with healed double blaze
36" I.Cedar, S.60°E., 16.5 ft. with healed blaze.

Note - See also C.S. maps M42-74 and M70-23. L. Moffit, L.S. 944 has the bearings reversed to the BTs on his map M70-23.

Corner is ± 150 ft. east of USFS Rd. #3132-C.

Fd. Ok by R. Brown, 1994-0036, 1/1994