

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Loyd R. Moffit - Umpqua Nat'l - June 1978 - M70-23

Set - A 2" pipe with 3" brass cap stamped: T31S R1W C¼ S19
PLS 944 1978"
A 8" Cedar bears N.66°W., 63.0', scribed C¼ S19 BT.
A 14" Fir bears N.22°E., 19.6', scribed C¼ S19 BT.

Maurice E. Farr, LS #1181 - Leonard Herzstein - Randy Lopez
For: USFS - Dec. 10, 1984 - C.S. 62/15-12

Found - 2½" outside dia. IP firmly set, projecting 2" above
a 3 ft. dia. mound of stone, with brass cap,
properly mkd, set by Moffit, LS. 944 in 1978.
14" D.Fir, N.22°E., 19.2 ft. (rec. 19.6 ft) with
scribe marks "C¼ S19 BT" visible on partially
healed double blaze.
8" I.Cedar, N.66°W., 63.0 ft. with scribe marks "C¼
S19 BT" visible on partially healed double blaze
with brass washer stamped "LS 944" nailed flush
to lower blaze. Tree has been cut off 12 ft.
above the ground by the Power company so it
wouldn't interfere with the power lines.
A steel fence post East, 3.8 ft. with USFS signs
#54-2 and 54-9 attached as a guard post.
New BT- I mark a new BT outside power line clearing to
replace NW BT:
A 16" P.Pine, S.73½°E., 32.0 ft. scribed "C¼ S19 BT"
on a single blaze with a brass washer stamped "LS
1181" nailed flush to base of blaze.
Corner is 900 ft. ± , N.15°E. from the junction of USFS Rd.
#1613-100 a State Highway 227, and 17 ft. north of east-west
barbwire fence under high tension power lines.

Fd. Ok by R. Brown, 1994-0036 - 2/1994

Leonard Herzstein, USFS - Witnessess: Lance Goucher & Andrew
Hellman - Feb. 15, 2007 - C.S. File 65/60-10A&B

Found - 2½" O.D. iron pipe, firmly set, projecting 2" above
a 3 ft dia mound of stone, w/3" dia brass cap
(properly) mkd.
BT marked by Moffit in 1978:
14" dia. I.Cedar, bears N.67°15'W., 63.0 ft (rec.
N.66°W.), with a healed double blaze.
Accessories by Farr in 1984:
15" dia P.Pine stump, bears S.72°45'E., 32.0 ft,
(rec. S.73½°E.) with no marks visible on a
burned partially healed double blaze. (cont)

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

4 ft tall steel fence post, bears East, 3.8 ft, with FS signs #54-2 "Property Boundary" and #54-9 "Land Survey Monument" attached.

New - 17" dia P.Pine, bears N.14°45'E., 36.0 ft, scribed "C $\frac{1}{4}$ S19 BT" on a single blaze with a $\frac{3}{4}$ " brass washer, stamped "LS 2150", nailed flush to the base of the blaze.

Note- I traversed the East-West centerline of section 19 to the Center-East 1/16 corner with a total station and I used the platted bearing of N.89°14'49"E. (M70-23) as my basis of bearings. Bearings for this renewal are rounded to the nearest 15 minutes. Trees are measured to the center of the root crown. The tree diameters are measured at breast height. This corner is under high tension powerlines and is approximately 15 feet northerly of an east-west fence line. The corner is approximately 920 feet, N. 15° E. from the junction of FS Road #1613-100 and County Road No. 1.