

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7476-7

Set ¼ sec. post, from which
A laurel, 18" dia., bears N.85°E., 85 lks.
An Oak, 12" dia., bears S.83°E., 85 lks.

Douglas Co. Surveyors Office - John M. Powell - 8/1968 - C.S. File 54/71-90

Reported as not found.
Both BTs to the east area to the east logged. All other trees in area opened at earlier date, squared post & location tag at approx. ¼ cor.

Jack Hoffbuhr - Umpqua Nat'l Forest - Oct. 18, 1972 - M42-80

Set -2½"x30" Galv. IP with 3" Brass Disk stamped as shown:

T31S R1W
¼ $\frac{S \ 7}{S \ 18}$
Ore. Lic. 222
1972

from which bears:
7" D.Fir BT bears N.49¾°W., 39.3 ft. scribed, "¼ S7 RS 222 BT"
10" D.Fir BT bears S.33°W. 37.6 ft., scribed, "¼ S18 RS 222 BT"

BLM dependent resurvey by Leonard E. Herzstein, LS USFS, under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO records Vol. 54 page(s) 20784

The ¼ sec. cor. of secs. 7 and 18, reestablished by proportionate measurement by Hoffbuhr, in 1972. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2½" iron post, firmly set, projecting 3" above ground and in a collar of stones, with brass cap (properly) mkd.
from which BTs mkd. by Hoffbuhr in 1972

A D.Fir, 15" dia., bears S.34°W., 37.1 ft., with healed blaze.
A D.Fir, 13" dia., bears N.49°W., 39.1 ft., with healed blaze.

Corner point lies East, 50 ft from downed barbed wire fence, fence bears N.8°E. and S.8°W.

continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher -
4/21/2015 - C.S. File 65/90-22

Found - A 3" brass cap on 2½" galvanized iron pipe,
projecting 1" above a mound of stone.
No trace found of a (18" laurel)1857
No trace found of a (12" oak)1857
A 15" fir with a healed double blaze, rec.
(N.49°45'W., 39.3') 1972, (N.49°W., 39.1') 2003
A 17" fir with a healed double blaze, rec. (S.33°W.,
37.6') 1972, (S.34°W., 37.1') 2003
No new accessories needed.

Corner maintenance/other info - clear brush from around
monument and to BT'S. Tie flagging to monument
and guard posts, paint BT faces & a 6" band at
head height, add new nails to existing BT tags &
add new tags where needed.

Geodetic coordinates -
LAT: N.42°53'14.148" LONG: W.122°52'24.222"
Datum - WGS 84
Source - USGS QUAD MAP, for navigation to corner.