

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Wm. Ruppert - For: USFS - Dec. 1977 - M65-60

-----  
Set - Brass cap stamped: T31S R1W C $\frac{1}{4}$  S7 PLS 866 1977.  
24" Cedar bears S.85°00'W., 94.0 ft. scribed "C $\frac{1}{4}$  S7 BT"  
12" Fir bears S.01°45'E., 43.4 ft. scribed "C $\frac{1}{4}$  S7 BT"  
Note- All monuments set on survey are set on 2"x30" galv.  
IP with 2 $\frac{1}{2}$ " Brass cap. All BT dimensions indicate  
the diameter of the tree at scribed area. All BT  
distances & bearing are from the center of the  
monument to the center of the tree. Scribed BTs have  
a brass washer stamped LS 866 nailed in lower blaze.

BLM dependent resurvey by Leonard E. Herzstein, LS USFS,  
under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO  
records Vol. 54 page(s) 20788-9

-----  
The center  $\frac{1}{4}$  sec. cor. of sec. 7, established by Wm Ruppert,  
in 1977, and accepted as the corner; monumented with a 2 $\frac{1}{2}$ "  
dia. iron post, firmly set, projecting 2" above ground and in  
a collar of stones, with brass cap mkd.

T31S R1W  
C $\frac{1}{4}$  . S7  
PLS 866  
1977

from which BTs mkd. by Ruppert in 1977  
A D.Fir, 15" dia., bears S.2°E., 43.0 ft., with healed  
double blaze.

A roothole, bears S.85°W., 94.0 ft., with incense cedar  
log, 24" dia., alongside with scribe marks C $\frac{1}{4}$  S7  
visible on partially healed double blaze.

and a new bearing tree

A D.Fir, 14" dia., bears S.76 $\frac{1}{2}$ °W., 41.1 ft., mkd. C $\frac{1}{4}$  S7 BT  
Corner point lies South, 3 ft of barbed wire fence, fence  
bears E and W.

Jonathan B. Drew, II, USFS - Reported by Andrew Hillman &  
Assisted by: Jacob Hunt - 9/7/2016 - C.S. File 65/93-45

-----  
Found - A 2 $\frac{1}{2}$ " galvanized iron pipe with a 2 $\frac{1}{2}$ " brass cap,  
projecting 2" above a mound of stone.

A root hole with a 24" cedar log with scribe marks  
visible on a partially healed single blaze along  
side, (S.85°W., 94.0 ft) 1977

A 16" fir with a healed double blaze, (S.1°45'E.,  
43.4 ft) 1977, (S.2°E., 43.0') 2003

A 15" fir with a healed single blaze, (S.76°30'W.,  
41.1 ft) 2003

continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No new accessories added.

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.

Lat: N.42°53'40.437" Long: W.122°52'24.072"

Datum: NAD83

Source: post processed resource grade, as reported by Jack Snyder.