

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7478

Set 1/4 sec. post, from which
A fir, 15" dia., bears N.45°E., 80 lks.
An Oak, 12" dia., bears S.70°W., 183 lks.

Glenn Baughman - For: Umpqua Nat'l Forest, Tiller Ranger Dist. - June 20, 1967 - C.S. 55/41-7 & M34-23

Set - 2½" bronze disk by single proper. method, from which
14" D.Fir bears N.24°W. 6.6 ft scribed ¼ cor. S6 & 7 BT
20" Maple bears S.15°W., 217.5 ft. scribed ¼ cor. S6 & 7 BT.

Wm. Ruppert - For: USFS - Dec. 1977 (added 5/20/2020) - M65-60

Bronze disk set in June, 1967 per M 34-23.
Bearing trees changed Jan. 4, 1978 per G. Baughman as follows:
21" D.Fir bears N.23°45'E., 22.5 ft. scribed ¼ Cor. S 6 & 7 BT.
17" D.Fir bears S.45°15'E., 19.3 ft. scribed ¼ Cor. S 6 & 7 BT.

Leonard Herzstein, USFS - Art Archiniega & Joe Richie - 10/7/1980 (added 5/20/2020) - C.S. file 61/11-28

Found - 2" d, IP with brass cap (properly) mkd, firmly set, projecting 4' above ground, set by Baughman in 1967
Baughman BTs -
A D.Fir, 21" d, N.24°15'E., 22.5 ft (rec. 17" d, 19.2 ft.) with healed blaze.
A D.Fir, 17" d, S.44°46'E., 19.3 ft (rec. 21" d, 22.5 ft) with healed blaze.

BLM dependent resurvey by Leonard E. Herzstein, LS USFS, under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO records Vol. 54 page(s) 20786

The ¼ sec. cor. of secs. 6 & 7, reestablished by proportionate measurement by Baughman, in 1967. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2" dia. iron post, firmly set, projecting 4" above ground, with brass cap (properly) mkd.

Continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Baughman in 1967 and altered on the plat in 1978

A D.Fir, 25" dia., bears N.23¼°E., 22.5 ft., with healed blaze.

A D.Fir, 21" dia., bears S.45¼°E., 18.9 ft., with healed blaze.

From this point, a 1¼" dia. iron axle with 3½" dia. gear, firmly set, leaning southerly, projecting 14 ins. above ground, established by person(s) unknown, bears N.80°47'30"E., 79.06 ft.

Jonathan B. Drew, II, USFS - Reported by: Andrew Hillman & Assisted by: Jacob Hunt - 8/26/2016 - C.S. File 65/93-48

Found - A 2½" galvanized iron pipe with a 2½" brass cap, projecting 9" above the ground. (properly mkd)
No trace fd of a (15" fir) 1857 (N.45°E. 52.8 ft) 1857
No trace fd of a (12" oak) 1857 (S.70°W. 120.8 ft) 1857
A 25" fir with a healed double blaze, (N.23°45'E., 22.5 ft) 1967 & 2003
A 23" fir with a healed double blaze, (S.45°15'E., 19.3 ft) 1967, (18.9 ft) 2003
A (1¼" iron axel with 3.5" gear) 2003, not searched for, (N.80°47'30"E., 79.06 ft) 2003

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.

Lat: 42°54'06.802" Long: 122°52'41.957"

Datum: NAD 83

Source: Post processed resource grade, as reported by Jack Snyder