

PRIMARY CORNER DESCRIPTION (WC) AP for ¼ Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7472

Marked a fir, 15" dia., from which
 A laurel, 12" dia., bears S.40°E., 20 lks.
 A laurel, 10" dia., bears N.35°W., 36 lks.
Line to the W of this stake would run into a deep canyon, unfit for settlement or cultivation.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7590)

The Witness cor. to the ¼ sec. cor., which is a fir, 15" dia., with marks grown over; from which
 A dead laurel, 12" dia., bears S.40°E., 20 lks., mkd: WC ¼ S BT. (Old BT)
 A dead laurel, 10" dia., bears N.35°W., 36 lks., mkd: WC ¼ S BT. (Old BT)
The bearing of the line from the cor. of secs. 29. 30. 31. & 32, to the WC to the ¼ sec. cor. bet. secs. 30 & 31 is S.89°42'W., from the witness cor. to the ¼ sec. cor., S.89°42'W., on a true line 8.64 chains.

Glenn Baughman - For: USFS - July 1979 - C.S. File 58/176-37

Found - 40" D. Fir, I opened and found scribe marks visible on a burnt face, from which:
 A root hole with 4"-8" Laurels growing out bears S.40°E., 13.2 ft
 A root hole with 4"-8" Laurels growing out bears N.35°W., 23.8 ft
Set - A 2"x30" iron pipe, 18" in the ground in a 3 ft dia. mound of stone with a 3" Brass Cap marked: T31S R1W AP S30 S31 1979 PLS 536
Monument set 2.50 feet East of center of corner tree, from which Brass Cap:
 A 6" D.Fir bears N.64°E, 34.4 ft, marked: "AP S30 BT" on a double blaze and nailed a Brass Washer stamped "LS 536" into lower blaze.
 A 10" D.Fir bears S.4°E, 102.7 ft, marked: "AP S31 BT" on a double blaze and nailed a Brass Washer stamped "LS 536" into lower blaze.