TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7471

Set ¼ sec. post, from which
A live oak, 6" dia., bears N.55°W., 32 lks.
A fir, 50" dia., bears S.85°E., 12 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7589)

The point for the ¼ sec. cor., which I locate by reference to the orig. BTs.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 31|S 32
1923

from which
A fir, 50" dia., bears S.85°E., 12 lks., mkd: ¼ S32 BT. (Old BT)
A live oak, 6" dia., bears N.55°W., 32 lks., mkd: ¼ S31 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-77

Found - GLO Brass Cap properly marked in 1922.
50" D.Fir, now 54" Stob, S.85°E., 7.9 ft., shows good bark scribing and good BT face.
6", now 10" Live Oak, N.55°W., 21.1 ft., shows scribing.
New BTs- 11" D.Fir S.5°E., 2.2 ft. mkd: ¼ S32 CS BT.
14" R.Fir N.57½°W., 10.6 ft. mkd: ¼ S31 CS BT.
Note - This ¼ corner lies 65 ft. N. of a ravine, large boulders around.

Ron Quimby - For: Cow Creek - 11/2017 - M171-36

Found - 1923 US GLO BCIP
6" now 13" live oak bears N.55°W., 21.1' healed scribe
11" now 18" D.Fir bears S.5°E., 2.2' healed scribe
Green metal T-Post w/National Forest tag bears North, 4.3'
Aluminum post bears South, 6.0'.