

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7471

Set post, cor. secs. 29, 30, 31, & 32, from which
A cedar, 18" dia., bears N.8°W., 20 lks.
A fir, 12" dia., bears S.40°W., 21 lks.
A fir, 20" dia., bears N.55°E., 37 lks.
A fir, 18" dia., bears S.80°E., 3 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7588)

The point for the cor. of secs. 29, 30, 31, and 32, which I locate by reference to the original bearing trees.
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 29, 30, 31, & 32, with brass cap mkd
T31S R1W
S 30|S 29
S 31|S 32
1923
from Which
A cedar, 20" dia., bears N.12°E., 65 lks. mkd. T31S R1W S29 BT. (New BT)
A fir, 18" dia., bears S.80°E., 3 lks., mkd. T31S R1W S32 BT. (Old BT.)
A fir, 30" dia., bears S.53°W., 28 lks., mkd. T31S R1W S31 BT (New BT)
A cedar, 18" dia., bears N.8°W., 20 lks., mkd. T31S R1W S30 BT. (Old BT)
The original BTs in secs. 29 and 31 are dead and fallen.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-78

Found - GLO Brass Cap properly marked in 1922.
20", now 25" Cedar, N.12°E., 42.9 ft., scribe visible.
18", now 30" D.Fir, S.80°E., 2.0 ft., shows good scar.
18", now 25" Cedar, N.8°W. 13.2 ft., scribe visible.
30" D.Fir, now stump, S.53°W., 13.2 ft., shows good scar.
New BT - 9" Cedar S.44°W., 15.0 ft. mkd: T31S R1W S31 CS BT.
All other bearing trees OK and Tagged.