TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7472

Set ¼ sec. post, from which
A fir, 18" dia., bears S.22°E., 25 lks.
A fir, 18" dia., bears N.60°W., 18 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7587-8)

The point for the ¼ sec. cor., which I locate with reference to the orig. BTs.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 30|S 29
1923

from which
A fir, 18" dia., bears S.22°E., 25 lks., mkd: ¼ S29 BT. (Old BT)
A fir, 18" dia., bears N.60°W., 18 lks., mkd: ¼ S30 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-80

Found - GLO brass cap properly marked in 1922.
18" now 28" D.Fir S.22°E., 16.5 ft. shows good scar.
No trace of NW BT, falls in old skid trail.
New BT - 6" Maple N.81°W., 30.4 ft., mkd: ¼ S30 CS BT.