

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7474

Set post, cor. secs. 17, 18, 19, & 20, from which
A fir, 12" dia., bears S.8°W., 33 lks.
A fir, 18" dia., bears S.5°E., 56 lks.
A fir, 20" dia., bears N.35°E., 26 lks.
A fir, 12" dia., bears N.40°W., * lks.
* No distance given in orig. line notes on line.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-102

Found - 12" D.Fir, now 28" Double Fir, S.8°W. 21.8 ft., opened for scribe "19" (Tried to count rings but too close)
18", now 30" D.Fir, S.5°E., 37.0 ft., shows good scar.
20" D.Fir, now snag, N.35°E., 19.8 ft. (Rec. 17.2), shows good scar.
No trace of NW BT.

Set - Brass Cap at Cor. Mkd: County Surveyors T31S R1W
Office S 18|S 17
1968 S 19|S 20

New BTs- 28" D.Fir N.83°W., 31.3 ft. mkd T31S R1W S18 CS BT.
6" Maple N.26°E., 30.0 ft. mkd. T31S R1W S17 CS PT.

Note - Call on creek 33.0 ft. north of corner is good.