

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7477  
-----

Set 1/4 sec. post, from which  
A fir, 12" dia., bears S.32°W., 70 lks.  
A pine, 24" dia., bears N.35°E., 59 lks.

John H. Markham, Jr. - For: Stomar Lbr. - Oct. 11, 1960 - C.S. File 51/142-1  
-----

Determined by OBT  
44" dead pine snag bears N.35°E., 38.9 ft. OBT fd. scribe.  
At corner point  
Set - 1 1/4"x36" steel shaft from which:  
36" Pine S.46°E., 47.0 ft., mkd: 1/4 S8 T31S R1W BT.  
12" Fir S.53°W., 26.6 ft., mkd: 1/4 S7 BT.  
10" B.Oak N.8°W., 71.5 ft., mkd: 1/4 S7 BT.  
Road bears North 37.0 ft.

Wm. Ruppert - For: USFS - Nov. 1977 - M65-50  
-----

Found - Burned snag, N.34°42'E., 39.0 ft. (old BT)  
30 P.Pine, S.43°53'E., 46.7 ft. scribe visible.  
15" D.Fir, S.55°28'W., 21.5 ft. good scar.  
18" D.Fir, N.87°33'W., 32.9 ft. good sear.  
12" B.Oak, N.07°09'W., 71.3 ft. good scar.  
Set - 2"x30" steel pipe with 2 1/2" Brass cap marked: T31S R1W 1/4 S7 S8 PLS 866 1977, alongside a 1 1/2" steel shaft found per C.S. 51/142.

BLM dependent resurvey by Leonard E. Herzstein, LS USFS, under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO records Vol. 54 page(s) 20789-90  
-----

The 1/4 sec. cor. of secs. 7 & 8, perpetuated by Markham, in 1960, and further perpetuated by Wm Ruppert, in 1977, monumented with a 2 1/2" dia. iron post, firmly set, projecting 6" above a collar of stones, with a brass cap (properly) mkd. from which the remains of an original bearing tree

A burnt P.Pine snag, 36" dia., bears N.35°E., 40.1 ft., with fragmentary scribe marks and chaining notch visible on previously opened lower blaze. (Record & dist. to notch 38.9 ft.)

and bearing trees mkd. by Markham in 1960

A P.Pine, 30" dia., bears S.44 1/2°E., 46.4 ft., with scribe marks 1/4 visible on partially healed double blaze.

A D.Fir, 18" dia., bears S.54°W., 22.0 ft., with healed double blaze. continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A D.Fir, 24" dia., bears N.87½°W., 32.7 ft., with scribe marks BT visible on lower bark blaze & a healed blaze.  
A B.Oak, 15" dia., bears N.7¼°W., 71.3 ft., with healed double blaze.

Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher -  
4/28/2015 - C.S. File 65/90-3

-----  
Condition report only

- Found - A 2½" brass cap on 2½" galvanized iron pipe, projecting 2" above a ring of stone.  
A 28" pine snag with scribe visible on a previously opened double blaze. (N.35°E., 38.9') 1857 (N.35°E., 40.1') 2003  
A 32" pine with scribe visible on a part. healed upper blaze, healed lower blaze (S.46°E., 47.0') 1960, (S.44°30'E., 46.4') 2003  
A 21" fir with a healed double blaze, leans heavy west. (S.53°W., 26.6') 1960, (S.54°W. 22.0') 2003  
A 26" fir with a healed single blaze & "B" bark scribe visible below. No original, (N.87°30'W. 32.7') 2003  
A 16" oak with a healed double blaze. (N.8°W., 71.5') 1960, (N.7°15'W., 71.3') 2003

No new accessories needed - No new measurements taken  
Corner maintenance/other info: Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

Geodetic coordinates:  
Latitude: N42°53'41.044" Longitude: W122°51'48.878"  
Datum: WGS 84  
Source: USGS Quad map, for navigation to corner.