

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6647)

Set post corner secs. 31, 32, 5 and 6, from which
A Fir 10" dia., bears S.35°W., 14 lks.
A Fir 6" dia., bears S.28°E., 22 lks.
A Fir 18" dia., bears N.20°W., 23 lks.
A Fir 24" dia., bears N.2°E., 33 lks.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1966 - C.S. File 54/28-3

Found - 10" Fir now 11", S.35°W., 9.2 ft., opened for scribe "6".
6" Fir now stump, S.28°E., 14.6 ft.
18" Fir now 27", N.20°W., 15.2 ft., bark scribed S31 BT scar.
24" Fir now stump, N.2°E., 21.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T30S R1W S 31 | S 32
T31S R1W S 6 | S 5
1966

New BTs- 11" D.Fir N.80°E., 40.8 ft. scribed T30S R1W S32 CS BT.
17" D.Fir S.52°E., 51.3 ft. scribed T31S R1W S5 CSBT
26" D.Fir S.72°W., 21.2 ft. scribed T31S R1W S6 CSBT

Glenn Baughman - For: U.S. Forest Service - July 1979 - C.S. File 58/176-36

Found - A 1" I.P. projecting 16" above the ground with a 2½" brass cap mkd. by the DCSO.
11" D.Fir with partially healed blaze, bears S.35°W., 9.2 ft.
28" D.Fir wind thrown stump, bears N.20°W., 15.2 ft.
24" D.Fir stump, bears N.2°E., 21.8 ft.
12" D.Fir with healed blaze, bears N.80°E., 40.8 ft.
18" D.Fir with healed blaze, bears S.52°E., 51.3 ft.
26" D.Fir with scribe marks visible on a partially healed blaze, bears S.72°W., 21.2 ft.
New BT - A 16" W.Fir bears N.56°W., 140.1 ft. I marked "T30S R1W S31 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T30-1

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Loyd R. Moffit - For: U.S. Forest Service - Dec. 1986 - C.S.
File 62/30-19

Found - 1966 DCSO 2½" brass cap on 1" I.P.
24" rotted Fir stump which bears N.02°E., 21.8 ft.
12" Fir which bears N.80°E., 40.8 ft. scar visible.
18" dead Fir which bears S.52°E., 51.3 ft., scribe
visible.
14" Fir which bears S.35°W., 9.2 ft. scar visible.
20" dead Fir which bears S.72°W., 21.2 ft. scribe
visible.
16" Fir which bears N.56°W., 140.1 ft. scribe
visible.
27" uprooted Fir which bears N.20°W., 15.2 ft.
24" Fir which bears N.89°W., 23.0 ft. scar visible.
(Original unknown)
New BT - 7" Cedar which bears S.40°E., 62.8 ft. from the
corner, scribed "T31S R1W S5 BT" with LS washer
No. 944 nailed to BT scribe.