

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7474-5

Set ¼ sec. post, from which
 An Oak, 15" dia., bears S.30°E., 37 lks.
 An Oak, 12" dia., bears N.88°W., 32 lks.

Douglas Co. Surveyors Office - John M. Powell - 8/1968 - C.S. File 54/71-103

Reported as not found.
Found Oak with good face to (S.30°E.) opened for old face & axe work but no scribe. Also found blazed trail with X on tree for line, area has a lot of axe work. Had good line - found sec. cor. on same line ½ mile to the west.

Jack A. Hoffbuhr - For: USFS - 10/9/1972 - M 42-75

Corner set by proportionate measurement.
Set - 2½" Brass Cap on 1" Galv. iron pipe stamped as shown:
 T31S R1W
 1/4 Cor $\frac{S\ 17}{S\ 20}$
 Ore Lic 222
 1972
from which bears:
 9" D.Fir BT bears N.5½°E., 20.7 ft. scribed ¼ S17 RS 222 BT.
 11" D.Fir BT bears S.3½°W., 7.8 ft. scribed ¼ S20 RS222 BT.