

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 17

Alias	Description

Jack Hoffbuhr - Umpqua Nat'l Forest - Oct. 1972 - M42-75  
-----  
Set - 2½"x30" Galv. IP with 3" Brass Disk in maintenance  
Mound, stamped as shown: T31S R1W  
C ¼ Sec 17  
Ore. Lic. 222  
1972  
from which  
12" D.Fir BT bears S.70½°E. 26.0 ft scribed C¼ S17 RS222 BT  
13" B.Oak BT bears S.54°W. 17.5 ft. scribed C¼ S17 RS222 BT

---

John Ransom, USFS - Crew: Jonathan Drew - 7/28/2014 (filed  
3/29/2017) - C.S. File 65/95-17  
-----  
Found - 3" brass cap on 2½" iron pipe, projecting 3" above  
concrete, concrete cylinder resides in 2½ ft tall  
by 3 ft wide mound of stone, very solid  
21" Fir S.72°E., 25.7 ft healed double blaze.  
14" Oak stub S.52°15'W., 17.4 ft 10 ft tall, healed  
upper blaze part. Healed lower blaze  
New - A 12" fir bears, South, 33.2 ft, mkd "C¼S17" "BT"  
on a double blaze.  
A 9" fir bears, N.57°W., 7.5 ft, mkd "C¼S17" "BT" on  
a double blaze.  
A 6" fir bears, N.58°15'E., 29.1 ft, mkd "X" "BT" on  
a double blaze.  
New accessories include a ¾" brass washer stamped  
"LS2561" set flush in lower face between "B" & "T"  
Note - Corner falls about 75 ft south of private logging  
road in area of large rocks, take 350 road to  
bermed spur road near end of 350 road  
maintenance. Follow private road easterly to wide  
pull off at switchback, corner is just south.  
Brush cleared around monument and to BTs "LAND LINE"  
flagging tied on monument and guard posts  
Property line maintained east .5 miles and west .5  
miles basis of bearing being platted bearing  
(N.89°47'W.) Using a property line post found to  
the east. Measurements by LEICA 1103+ Total  
Station with red laser to aluminum nail set at  
side center.