



TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note: "COUNTY SURVEYORS OFFICE" & date stamp not oriented north, as shown below. Cap shows R1W as re-stamped by Fanning in 2001.

A 15" oak snag with scribe visible on a partially healed double blaze, face & scribe is rotted.  
(N.32°E., 23.8') 1857 (N.33°35'E., 24.5') 1977

A 28" Madrone with a healed double blaze bears,  
(S.4°30'E., 24.1') 1966, (S.2°E., 23.7') 1977

A 22" Fir with a healed double blaze bears,  
(N.67°E., 14.3') 1966, (N.69°E., 14.4') 1977

No new accessories

Corner maintenance/other info: clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT Tags & add new tags where needed.

Geodetic coordinates:  
Latitude: N.42°53'14.854"      Longitude: W 122°51'12.244"  
Datum: WGS 84  
Source: USGS Quad map, for navigation to corner.